


product type designation

product description

IE FC RJ45 Plug 180 (2x2)

RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP cable 2x 2; 180° cable outlet 1 pack = 10 units.



suitability for use

For connection to IE FC TP cables 2x2, suitable for fast assembly with the FastConnect system

transfer rate

transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s

interfaces

number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

4
1

type of electrical connection

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22
RJ45 connector

type of electrical connection / FastConnect

Yes

mechanical data

material / of the enclosure

metal

number of reuses

10

locking mechanism design

other

design, dimensions and weights

type of cable outlet

180° cable outlet

width

13.7 mm

height

16 mm

depth

55 mm

net weight

35 g

connectable cable cross-section

6.5 ... 6.5 mm

connectable conductor cross-section

0.33 mm²

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C
-40 ... +85 °C
-40 ... +85 °C

relative humidity

- at 25 °C / without condensation / during operation / maximum

95 %

protection class IP

IP20








product features, product functions, product components / general

product feature

- PoE capability
- PoE+capability
- silicon-free

Yes
Yes
Yes

product component	
• strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• cULus approval	Yes
• railway application in accordance with EN 50155	No
standard for structured cabling	Cat5
reference code	
• according to IEC 81346-2:2019	XGA
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	
• total	0.277 kg
• during manufacturing	0.263 kg
• during operation	0.0086 kg
• after end of life	0.0062 kg
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAX-Download-Manager	https://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)

Approvals / Certificates			
General Product Approval	Test Certificates	Marine / Shipping	
Declaration of Conformity  	Miscellaneous 		
Marine / Shipping	Environment	Industrial Communication	
 	Confirmation 	PROFINET	

last modified:

12/9/2024 