



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8083-1SN00-1LA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	5.3	10.0	17.0	335	168.9	5,000	40	41.0	15,000	19.0	23	0.870	0.690	9.7
	BLM/SLM 400V	4.8	10.0	17.0	300	152.3	4,500	40	41.0	15,000	19.0	23	0.860	0.700	9.5
	ALM/BLM/SLM 480V	5.5	10.0	16.5	350	185.7	5,500	40	41.0	15,000	19.0	23	0.870	0.710	9.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	80
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder 19 bit without commutation position (encoder IN19DQ)

External fan

Max. power consumption

1 AC 230 V / 50 Hz (±10%)	0.20 A
1 AC 230 V / 60 Hz (±10%)	0.16 A
1 AC 265 V / 60 Hz (±10%)	0.19 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	64 kgcm ²
Weight (approx.)	32 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk803

Cooling data and sound pressure level

Airflow, min.	0.02 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	95 Pa







Confie a titre de secret d'entreprise. Tous droits reserves.
Confidado como secreto industrial. Nos reservados todos los derechos
Comunicado como segredo empresarial. Reservados todos os direitos

Weitergabe sowie Vervielfaeltigung dieser Unterlage. Verwer-
tung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht
ausdruecklich zugestanden. Zuwiderhandlungen verpflichten
zu Schadenersatz. Alle Rechte vorbehalten, insbesondere fuer
den Fall der Patenterteilung oder GK-Entragung.

The reproduction or use of this document or its
contents is not permitted without express written authority.
Diffenders will be liable for damages. All rights, including rights
created by patent grant or registration of a utility model or design,
are reserved.

Copyright© Siemens AG 2005
Cada-drawing do not make any
manual changes

DE - shaft extension
version with featherkey



Type of construction: IM B3 (IM V5, IM V6) / Type of protection: IP55

		1PH8083-1SN00-1LA1	
Terminal box	gk803	-	
Weight	32 kg		
Unit	mm (in)		
Date	4/11/23	DT	
SIEMENS AG		not toleranced dimensions: ± 1	