Technical Specifications for 2711E-K14C6

| Memory | 2.25 MB | |
|----------------------------|--|--|
| Weight: | 43.5 lbs (19.7 kg). | |
| Input Voltage range: | 85264V AC, 4763 Hz | |
| Communication ports: | DH+ / RIO | |
| Resolution: | 640 x 480 | |
| Display Type: | Color Active Matrix TFT screen | |
| Window: | clear, hard-coated, scratch-resistant polyester over chemically strengthened glass | |
| Key panel: | sealed, stainless steel dome membrane switches with tactile feedback and an actuation force of 1 lb. (0.455 kg), mounted on the key panel's reinforced plastic bezel, protected with a hard-coated, scratch-resistant polyester surface. Keys are rated for 2,000,000 presses. | |
| Compatible Controllers: | PLC5, SLC500, CompactLogix, ControlLogix controllers | |
| Product Type: | PanelView 1400E | |
| Product Family: | PanelView Enhanced | |

| Brand | Allen-Bradley |
|---------------------------|-----------------------|
| Manufacturer: | Rockwell Automation |
| Part Number/Catalog No. | 2711E-K14C6 |
| Product Line | Panelview 2711E |
| Display Size | 14-inch |
| Display Color | Color |
| Input Type | Keypad |
| Communication | DH+ and Remote I/O |
| Input Voltage | 180-264V AC |
| Backlight | 6189-NL2 |
| Product Lifecycle Status* | Discontinued/Obsolete |