## SIEMENS

## Data sheet

## 6XV1822-5BE30

product type designation product description

## 7/8 inch connecting cable

Plug-in cable (5-core), preferred length, preassembled with two 5-pole 7/8 inch male/female-contact connectors

7/8" plug-in cable for Power supply of the ET 200, pre-assembled cable with 2 7/8" connectors, 5-pole, 0.3 m .



suitability for use	Power supply of ET 200 modules with 7/8 inch power port to IP 65 degree of protection
cable designation	L-Y11Y-Z 5x1x1.5 GR
wire length	0.3 m
electrical data	
insulation resistance coefficient	1 GΩ·m
operating voltage / RMS value	600 V
conductor cross section / of the power line	1.5 mm <sup>2</sup>
continuous current / of the power lines	16 A
mechanical data	
number of electrical cores	5
type of electrical connection	7/8 inch - 180
outer diameter	
of inner conductor	1.55 mm
of the wire insulation	2.73 mm
of cable sheath	10.5 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.3 mm
design of stranding element	Pairs
conductor class	5
material	
of the conductor	CU, blank
of the wire insulation	PVC
of cable sheath	PUR
product component / PE connection	Yes
marking / of cores	Color, digits
color	
<ul> <li>of the power line insulation</li> </ul>	black
of cable sheath	gray
bending radius	
<ul> <li>with single bend / minimum permissible</li> </ul>	27 mm
<ul> <li>with multiple bends / minimum permissible</li> </ul>	63 mm
<ul> <li>with continuous bending</li> </ul>	75 mm
number of bending cycles	5000000; For use in cable carriers, for 5 million bending cycles with a bending radius of 75 mm, an acceleration of 4 m/s <sup>2</sup> and a speed of 180 m/min
tensile load / maximum	500 N
weight per length	149 kg/km
plug	
type of plug interlock	screwed

design of plug-in connection	7/8 inch - 180	
connector coding	7/8 inch	
ambient conditions		
ambient temperature		
during operation	-40 +80 °C	
during storage	-40 +80 °C	
during transport	-40 +80 °C	
during installation	-40 +80 °C	
fire behavior	Flame-resistant acc. to IEC 60332-1	
chemical resistance		
• to mineral oil	resistant	
	resistant	
• to grease radiological resistance / to UV radiation	resistant	
protection class IP	IP65 / 67	
·		
product features, product functions, product components / ge		
product feature		
halogen-free	No	
silicon-free	Yes	
standards, specifications, approvals		
UL/ETL listing / 300 V Rating	No	
UL/ETL style / 600 V Rating	Yes	
certificate of suitability	UL2238 E300110	
EAC approval	Yes	
RoHS conformity	Yes	
reference code		
according to IEC 81346-2:2019	WDB	
further information / internet links		
internet link		
<ul> <li>to website: Selection guide for cables and connectors</li> </ul>	https://support.industry.siemens.com/cs/ww/en/view/109766358	
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	https://www.siemens.com/tstcloud	
<ul> <li>to website: Industrial communication</li> </ul>	https://www.siemens.com/simatic-net	
<ul> <li>to web page: SiePortal</li> </ul>	https://sieportal.siemens.com/	
<ul> <li>to website: Image database</li> </ul>	https://www.automation.siemens.com/bilddb	
<ul> <li>to website: CAx-Download-Manager</li> </ul>	https://www.siemens.com/cax	
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com	
security information		
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)	
Approvals / Certificates		
General Product Approval	Environment	
EG-Konf.	Manufacturer Declara- <u>tion</u> Confirmation	
Industrial Communication		
CV1///0005DF00	Subject to change without potic	

last modified:

8/18/2024 🖸