SIEMENS

Data sheet 6XV1830-2AN10

product type designation

product description

suitability for use

PROFIBUS Cable 830-2

Plug-in cable comprising PROFIBUS standard cable, preferred length, preassembled with two 9-pole connectors

plug-in cable 830-2 for PROFIBUS, pre-assembled cable with two D-sub connectors 9-pole, Terminating resistors connectable, 10 m.

Cable for connecting PROFIBUS stations (e.g. HMI) to automation devices



| culture for doo | casic for confidency i from 1200 diamond (e.g. 1 min) to diatomication devices |
|---|--|
| cable designation | 02YSY (ST) CY 1x2x0,64/2,55-150 VI KF 40 FR |
| wire length | 10 m |
| electrical data | |
| number of electrical connections | 2 |
| attenuation factor per length | |
| • at 9.6 kHz / maximum | 0.0025 dB/m |
| • at 38.4 kHz / maximum | 0.004 dB/m |
| • at 4 MHz / maximum | 0.022 dB/m |
| • at 16 MHz / maximum | 0.042 dB/m |
| operating voltage | |
| RMS value | 80 V |
| mechanical data | |
| number of electrical cores | 2 |
| design of the shield | Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires |
| outer diameter | |
| of inner conductor | 0.65 mm |
| of the wire insulation | 2.55 mm |
| of the inner sheath of the cable | 5.4 mm |
| material | |
| of the wire insulation | polyethylene (PE) |
| of the inner sheath of the cable | PVC |
| color | |
| of the insulation of data wires | red/green |
| bending radius | |
| with single bend / minimum permissible | 37.5 mm |
| with multiple bends / minimum permissible | 75 mm |
| weight per length | 80 kg/km |
| ambient conditions | |
| ambient temperature | |
| • note | Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472 |
| fire behavior | flame resistant according to IEC 60332-3-24 (Category C) and UL 1685 (CSA FT 4) |
| chemical resistance | |
| • to mineral oil | oil resistant according to IEC 60811-2-1 (4 h / 70°C) |
| • to water | conditional resistance |

| radiological resistance / to UV radiation | resistant | |
|---|-----------------------------------|--|
| protection class IP | IP20 | |
| standards, specifications, approvals | | |
| UL/ETL listing / 300 V Rating | Yes; c(UL)us, CMG / CL3 / Sun Res | |
| UL/ETL style / 600 V Rating | Yes | |
| certificate of suitability | | |
| EAC approval | Yes | |
| CE marking | Yes | |
| RoHS conformity | Yes | |
| Marine classification association | | |
| American Bureau of Shipping Europe Ltd. (ABS) | No | |
| French marine classification society (BV) | No | |
| Det Norske Veritas (DNV) | No | |
| Germanische Lloyd (GL) | No | |
| Lloyds Register of Shipping (LRS) | No | |
| Nippon Kaiji Kyokai (NK) | No | |
| Polski Rejestr Statkow (PRS) | No | |
| reference code | | |
| according to IEC 81346-2 | WG | |
| according to IEC 81346-2:2019 | WGB | |
| further information / internet links | | |
| | | |

internet link

• to website: Selection guide for cables and connectors

• to web page: selection aid TIA Selection Tool

• to web page: SiePortal

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

https://support.industry.siemens.com/cs/ww/en/view/109766358

https://www.siemens.com/tstcloud

https://sieportal.siemens.com/

https://www.automation.siemens.com/bilddb

https://www.siemens.com/cax

https://support.industry.siemens.com

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval



Declaration of Conformity





Manufacturer Declaration



Environment

Confirmation

last modified: 8/8/2024 🖸

