

PRODUCT-DETAILS

ACS880-01-260A-5 ACS880-01-260A-5, PLd 200HP, I2LD 260A



| eneral Information | |
|-------------------------|------------------|
| Global Commercial Alias | ACS880-01-260A-5 |
| Product ID | 3AUA0000143782 |
| ABB Type Designation | ACS880-01-260A-5 |
| EAN | 6438177474739 |

Catalog Description ACS880-01-260A-5, PLd 200HP, I2LD 260A

The ACS880-01 drives are customized to meet the particular needs of specific industries, such as oil and gas, mining, metals, chemicals, cement, power plants, material handling, pulp and paper, sawmills, marine, water and wastewater, food and beverage, and automotive. They can control a wide range of applications, including cranes, extruders, winches, winders, conveyors, mixers, compressors, centrifuges, test benches, elevators, extruders, pumps and fans. The ACS880-01 comes in one compact package for easy installation and commissioning. The drive can be installed on the wall as standard and in a cabinet as an option. The drive offering includes enclosure classes up to IP55, making it suitable for most environments and installations. ACS880-01 drives have all the essential features built-in. These features include as standard a choke for harmonic filtering as well as options like a brake chopper, EMC filter and communication protocol adapter, functional

safety, external output filters and I/O extension modules.

Long Description

Ordering

Country of Origin United States (US)

Customs Tariff Number 85352100

| Invoice Description | ACS880-01-260A-5, PLd 200HP, I2LD 260A |
|----------------------------------|---|
| Made To Order | No |
| Minimum Order Quantity | 1 piece |
| Order Multiple | 1 piece |
| Quote Only | No |
| Selling Unit of Measure | piece |
| | |
| Dimensions | |
| Product Net Weight | 154 lb |
| Product Net Depth / Length | 15.2 in |
| Product Net Height | 38 in |
| Product Net Width | 11.8 in |
| Package Level 1 Units | 1 carton |
| Technical | |
| Number of Phases | 3 |
| Degree of Protection | IP21 |
| Enclosure Type NEMA | Type1 |
| Frequency (f) | 50/60 Hz |
| Frame Size | R8 |
| Input Voltage (U _{in}) | 380 500 V |
| Output Current, Light- | 260 A |
| Overload Use (I _{LD}) | |
| Output Power, Light- | 200 Hp |
| Overload Use (P _{LD}) | |
| Additional Information | |
| Product Name | AC Drive |
| | |
| Classifications | |
| UNSPSC | 39122001 |
| En in an artel | |
| Environmental | |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

ACS880-01-260A-5

Categories

