



Figure similar

accessory for Switch disconnecter with fuses In-line design, pluggable current transformer 150/1 A, Cl. 1, 2.5 VA

| Model                                      |        |                                                   |                   |
|--------------------------------------------|--------|---------------------------------------------------|-------------------|
| product brand name                         |        | SENTRON                                           |                   |
| product designation                        |        | Current transformer                               |                   |
| design of the product                      |        | accessory for switch disconnecter with fuses 3NJ6 |                   |
| operating voltage                          |        | 0.72 kV                                           |                   |
| insulation voltage rated value             |        | 3 kV                                              |                   |
| designation of overcurrent limiting factor |        | FS 5                                              |                   |
| current                                    |        |                                                   |                   |
| • at input rated value                     | 150 A  |                                                   |                   |
| value range of the operating frequency     |        | 50/60 Hz                                          |                   |
| Protection class                           |        |                                                   |                   |
| protection class IP                        |        | IP20                                              |                   |
| Mechanical Design                          |        |                                                   |                   |
| height                                     |        | 65 mm                                             |                   |
| width                                      |        | 44 mm                                             |                   |
| depth                                      |        | 30 mm                                             |                   |
| diameter of inlet opening                  |        | 21 mm                                             |                   |
| net weight                                 |        | 192 g                                             |                   |
| Environmental conditions                   |        |                                                   |                   |
| ambient temperature during operation       |        |                                                   |                   |
| • minimum                                  | -10 °C |                                                   |                   |
| • maximum                                  | 55 °C  |                                                   |                   |
| Approvals Certificates                     |        |                                                   |                   |
| General Product Approval                   |        | EMV                                               | Test Certificates |



[Confirmation](#)



[Type Test Certificates/Test Report](#)

| other                        | Environment                   |                                             |
|------------------------------|-------------------------------|---------------------------------------------|
| <a href="#">Confirmation</a> | <a href="#">Miscellaneous</a> | <a href="#">Environmental Confirmations</a> |

| Further information          |
|------------------------------|
| Information on the packaging |

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NJ6920-3BE11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NJ6920-3BE11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NJ6920-3BE11](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ6920-3BE11)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

---

last modified:

8/16/2023 

