

PRODUCT-DETAILS

3GBP162430-ADL

IE3 Premium Efficiency Cast Iron Motor, 18.5 kW, 400 V (3GBP162430-ADL)



General Information

Product ID	3GBP162430-ADL
ABB Type Designation	M3BP 160MLC 4
Catalog Description	IE3 Premium Efficiency Cast Iron Motor, 18.5 kW, 400 V (3GBP162430-ADL)

Additional Information

ABB Type Designation	M3BP 160MLC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6209/C3
Connection Configuration	D
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	18.50 kW	1473 r/min	20.30 A	0.820	92.60 %	119.93 N-m	8.30
D	--	50 Hz	400 V	18.50 kW	1473 r/min	35.10 A	0.820	92.60 %	119.93 N-m	8.30
D	--	50 Hz	415 V	18.50 kW	1475 r/min	35.10 A	0.790	92.60 %	119.77 N-m	8.60
D	--	60 Hz	440 V	18.50 kW	1774 r/min	31.90 A	0.820	92.40 %	99.58 N-m	8.60
D	--	60 Hz	460 V	18.50 kW	1777 r/min	31.20 A	0.800	92.40 %	99.42 N-m	9.20

Frame Material	Cast Iron
Frequency (f)	50 Hz
Gross Weight	190 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.6 % Partial Load (75%) 93.1 % Partial Load (50%) 92.7 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 92.4 % Partial Load (75%) 92.6 % Partial Load (50%) 91.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
Invoice Description	M3BP 160MLC 4
Made To Order	No
Medium Description	18.5kW, 4 Poles, Frame Size 160, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GBP162430-ADL)
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Output Power	18.5 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	681 mm
Product Net Height	421 mm
Product Net Weight	180 kg
Product Net Width	310 mm
Product Type	5BP3 M3BP CI
Quote Only	No
Replaced Product ID (OLD)	3GBP162053-ADL
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Short Description	18.5kW, 4P, Frame Size 160, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	D

WEEE Category

4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Cast Iron Motors

