

### product type designation

### product description

### Cable RS422, M12 / M12

Highly flexible communication line (6-core)

SIMATIC RF, MV plug-in cable, pre-assembled, between ASM 456, RF160C, RF170C, RF18XC and reader, or extension cable for ASM 456, RF160C, RF170C, RF18XC with RF, MV, MOBY PUR, trailing, length 5 m.



### suitability for use

Plug-in or extension cable for connecting a reader to a communication module

### cable designation

L-YC11Y 6x1x0.25 6x24AWG CM

### wire length

5 m

### electrical data

#### number of electrical connections

2

#### type of electrical connection

M12 (male, 8 pin, straight) / M12 (female, 8 pin, straight)

#### loop resistance per length / maximum

160 mΩ/m

#### insulation resistance coefficient

20 GΩ·m

#### operating voltage

##### • maximum

300 V

### mechanical data

#### number of electrical cores

6

#### design of the shield

Braided shield made of tin-plated copper wires

#### outer diameter

##### • of cable sheath

5.4 mm

#### symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

#### material

##### • of the wire insulation

PVC

##### • of cable sheath

PUR

#### color

##### • of the insulation of data wires

DIN 47100

##### • of cable sheath

Black

#### bending radius

##### • with single bend / minimum permissible

21.6 mm

##### • with multiple bends / minimum permissible

43 mm

##### • with continuous bending

75 mm

#### number of bending cycles

3000000

#### tensile load / maximum

200 N

#### weight per length

45 kg/km

### ambient conditions

#### ambient temperature

##### • during operation

-30 ... +80 °C

##### • during storage

-30 ... +80 °C

##### • during transport

-30 ... +80 °C

##### • during installation

-30 ... +80 °C

#### fire behavior

flame resistant according to IEC 60332-1-2

#### class of burning behaviour / according to EN 13501-6

Eca

#### chemical resistance

<ul style="list-style-type: none"><li>• to mineral oil</li><li>• to grease</li></ul>	resistant				
radiological resistance / to UV radiation	resistant				
product features, product functions, product components / general					
product feature <ul style="list-style-type: none"><li>• halogen-free</li><li>• silicon-free</li></ul>	No Yes				
standards, specifications, approvals					
UL/ETL listing / 300 V Rating	Yes; CM (only cable without plug)				
certificate of suitability <ul style="list-style-type: none"><li>• EAC approval</li></ul>	Yes				
reference code <ul style="list-style-type: none"><li>• according to IEC 81346-2</li><li>• according to IEC 81346-2:2019</li></ul>	WG WGB				
further information / internet links					
internet link <ul style="list-style-type: none"><li>• to website: Selection guide for cables and connectors</li><li>• to web page: selection aid TIA Selection Tool</li><li>• to web page: SiePortal</li><li>• to website: Image database</li><li>• to website: CAX-Download-Manager</li><li>• to website: Industry Online Support</li></ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>				
security information					
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="https://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7)				
Approvals / Certificates					
General Product Approval	EMV	Environment			
 EG-Konf.		 CCC		<a href="#">KC</a>	<a href="#">Confirmation</a>

last modified:

8/8/2024 