

product type designation

product description

Power Connecting Cable M12-180/M12-180

Flexible plug-i...able outl001

Power connecting cable M12-180/M12-180 for the power supply of the ET 200, pre-assembled cable with M12 plug and M12 socket, A-coded, 4-pole, 2.0 m.



suitability for use

Plug-in cable for connecting 24 V power supply to ET 200 & XP-200 with IP 65/67 degree of protection

cable designation

LI9YH-Y 4x0.75

wire length

2 m

electrical data

operating voltage / RMS value

300 V

conductor cross section / of the power line

0.75 mm²

mechanical data

number of electrical cores

4

type of electrical connection

M12-180

outer diameter

• of inner conductor

1.1 mm

• of the wire insulation

1.7 mm

• of cable sheath

5.7 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

design of stranding element

Pairs

conductor class

5

material

• of the conductor

CU, blank

• of the wire insulation

PP

• of cable sheath

PVC

product component / PE connection

No

marking / of cores

Color

color

• of the power line insulation

brown / white / blue / black

• of cable sheath

gray

bending radius

• with single bend / minimum permissible

57 mm

• with multiple bends / minimum permissible

57 mm

• with continuous bending

57 mm

number of bending cycles

100000

tensile load / maximum

15 N

weight per length

54 kg/km

plug

type of plug interlock

screwed

design of plug-in connection

M12-180

connector coding

M12

connector coding / of the M12 circular connector

A coded

| ambient conditions | |
|---|--|
| ambient temperature | |
| • during operation | -25 ... +80 °C |
| • during storage | -25 ... +80 °C |
| • during transport | -25 ... +80 °C |
| • during installation | 80 °C |
| ambient condition / for operation | With moving applications, the permissible operating temperature range is -5 to +80 degrees Celsius |
| fire behavior | Flame-resistant acc. to UL 758 (CSA FT 1) |
| chemical resistance | |
| • to mineral oil | Conditional resistance |
| • to grease | Conditional resistance |
| radiological resistance / to UV radiation | not resistant |
| protection class IP | IP65 / 67 |

product features, product functions, product components / general

| | |
|-----------------|-----|
| product feature | |
| • halogen-free | No |
| • silicon-free | Yes |

standards, specifications, approvals

| | |
|---------------------------------|--|
| UL/ETL listing / 300 V Rating | Yes; AWM 2464/10493 AWM I/II A/B 80°C 300V FT1 |
| certificate of suitability | UL2238 E300110 |
| • EAC approval | Yes |
| • RoHS conformity | Yes |
| reference code | |
| • according to IEC 81346-2:2019 | WDB |

further information / internet links

| | |
|---|---|
| internet link | |
| • to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| • to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| • to website: Industrial communication | https://www.siemens.com/simatic-net |
| • to web page: SiePortal | https://sieportal.siemens.com/ |
| • to website: Image database | https://www.automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | https://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

security information

| | |
|----------------------|---|
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7) |
|----------------------|---|

Approvals / Certificates

| General Product Approval | Environment |
|--------------------------|-------------|
|--------------------------|-------------|



EG-Konf.

[Declaration of Conformity](#)



CCC

[Manufacturer Declaration](#)

[Confirmation](#)

Industrial Communication

last modified:

8/18/2024 