SIEMENS

Data sheet   **6GK1901-0DB20-6AA8**

product type designation	**IE FC M12 Plug PRO (PROFINET)**
product description	M12 connector with high protection, 4-pole, D-coded
	Industrial Ethernet FastConnect M12 plug PRO 2x2 M12 plug-in connector with rugged metal enclosure and FC connection method, with axial cable outlet (D-coded) 1 pack=8 units for SCALANCE X208 PRO and ET 200 PRO PN.

suitability for use	For connecting electrical cables to SCALANCE X208PRO, ET200 PRO PN or ET200 eco PN for fast assembly with the FastConnect system

transfer rate	
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s

interfaces	
number of electrical connections	
● for Industrial Ethernet FC TP cables	4
● for network components or terminal equipment	1
type of electrical connection	
● for Industrial Ethernet FC TP cables	integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22
type of electrical connection / FastConnect	Yes

mechanical data	
material / of the enclosure	metal
number of reuses	10
locking mechanism design	Screwed joint
tightening torque / for M12 round connector / maximum	0.6 N·m
connector coding / of the M12 circular connector	D

design, dimensions and weights	
type of cable outlet	180° cable outlet
width	19 mm
height	19 mm
depth	73 mm
net weight	40 g
connectable cable cross-section	6.5 ... 6.5 mm
connectable conductor cross-section	0.33 mm²

ambient conditions	
ambient temperature	
● during operation	-40 ... +85 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
chemical resistance	
● to water	resistant
protection class IP	IP65/67

product features, product functions, product components / general	
product feature	

● PoE capability	Yes	
● PoE+capability	Yes	
● silicon-free	Yes	
product component		
● strain relief	Yes	

standards, specifications, approvals

certificate of suitability		
● RoHS conformity	Yes	
● UL approval	Yes	
● cULus approval	Yes	
● railway application in accordance with EN 50155	No	
standard for structured cabling	Cat5	
reference code		
● according to IEC 81346-2:2019	XGA	

standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes	
global warming potential [CO2 eq]		
● total	0.32 kg	
● during manufacturing	0.28 kg	
● during operation	0.01 kg	
● after end of life	0.03 kg	

further information / internet links

internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval				Marine / Shipping	
Declaration of Conformity	CCC	EAC	UL	DNV	Lloyd's Register LRS

Marine / Shipping	Environment		Industrial Communication
RINA	Confirmation	EPD	PROFINET

last modified: 12/9/2024 ⬈

1/20/2025