



INSTA contactor with 2 NO contacts Contact for 230 V AC, 400V 20A
Control AC/24 V DC

Model	
product brand name	SETRON
product designation	Insta contactor
design of the product	2 NO contacts
type of voltage / of the operating voltage	AC
type of voltage / of the operating voltage / for actuation	AC/DC
Supply voltage	
operating voltage / rated value	
• minimum	230 V
• maximum	230 V
Protection class	
protection class IP	IP20
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.7 W
Current	
operational current / at AC / rated value	20 A
Main circuit	
operational current / rated value	20 A
Control current	
control supply voltage	
• rated value	24 V
• rated value / maximum	24 V
• at DC / rated value	24 V
Product details	
product component / slide for manual operation	No
number of NC contacts	0
number of NO contacts	2
product extension / installable / supplementary devices	Yes
Mechanical Design	
height	90 mm
width	17.5 mm
depth	71 mm
installation depth	64 mm
number of modular width units	1
net weight	141 g
Certificates	

reference code			
• acc. to DIN EN 61346-2 • acc. to IEC 81346-2	Q		
	Q		
General Product Approval		Declaration of Conformity	Test Certificates
			
	Miscellaneous		Special Test Certificate

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5000-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT5000-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5000-2

Tender specifications

<http://www.siemens.com/specifications>



