



SIMATIC DP,
BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 90
DEGREE ANGLE OUTGOING CABLE,
15,8 X 64 X 35,6 MM (WXHxD),
TERMINAT. RESIST. WITH ISOLAT. FUNCTION,
WITHOUT PG SOCKET

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Mechanical data

material / of the housing

plastic

Design, dimensions and weight

Width

15.8 mm

Height

64 mm

Depth

35.6 mm

Net weight

10 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-40 ... +70 °C

-40 ... +70 °C

Protection class IP

IP20

Product properties, functions, components / general

Product feature / [not supplied - silicon-free]

Yes

Composant produit

- [nicht versorgt - PG-Anschlussbuchse]

No

- décharge de traction

Yes

Standards, specifications, approvals

Verification of suitability

- RoHS conformity

Yes

- UL-registration

Yes

letzte Änderung:

Mar 12, 2012