

PRODUCT-DETAILS

PSTB840-600-70

PSTB840-600-70 Softstarter



General Information

Extended Product Type	PSTB840-600-70
Product ID	1SFA894019R7000
EAN	7320500255674
Catalog Description	PSTB840-600-70 Softstarter
Long Description	Softstarter PSTB840-600-70 for max 600V main voltage and 110 - 240V 50/60Hz control supply voltage

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	8503009999

Popular Downloads

Data Sheet, Technical Information	1SFC132005C0201
Instructions and Manuals	1SFC132003M0201

Dimensions

Product Net Width	436 mm
Product Net Height	515 mm
Product Net Depth / Length	381 mm
Product Net Weight	60 kg

Technical

Rated Operational Voltage	Main Circuit 208 ... 600 V AC
Rated Control Supply Voltage (U_s)	100 ... 250 V AC
Rated Control Circuit Voltage (U_c)	DC Operation 24 V
Rated Frequency (f)	50/60 Hz Main Circuit 50 / 60 Hz
Rated Operational Power - In-Line Connection (P_e)	(400 V) 450 kW (500 V) 600 kW
Rated Operational Current - In-Line Connection (I_e)	840 A
Rated Operational Power - Inside Delta Connection	at 400 V 800 kW at 500 V 1000 kW
Rated Operational Current - Inside Delta Connection	1455 A
Service Factor Percentage	115 %
Overload Protection	Build-in electronic overload protection
Integrated Electronic Overload	Yes
Adjustable Rated Motor Current I_e	30 ... 115 %
Starting Capacity at Maximum Rated Current I_e	3xle for 15s
Ramp Time	0 ... 120 second [unit of time] 1 ... 120 second [unit of time]
Initial Voltage During Start	30 ... 70 %
Step Down Voltage Special Ramp	100 ... 30 %
Current Limit Function	1.5 ... 7xle
Switch for Inside Delta Connection	Yes
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	Yes
Overload Signal Relay	Yes
Analog Outputs	0...10 volts 0...20 mA 4...20 mA
Signal indication ready to start/standby ON (LED)	Green
Signal indication protection (LED)	Yellow
Signal indication fault (LED)	Red

Number of Starts Per Hour at 3.5*1e for 7 sec. 50% ON Time 50% OFF Time	10
Communication	FiledBusPlug(Standard)
Degree of Protection	IP00
Terminal Type	Main Circuit: Bars
Connecting Capacity Main Circuit	Hole Diameter 12.5 mm Width and Thickness 40x6 mm
Connecting Capacity Control Circuit	Rigid 1 x 2.5 mm² Rigid 2 x 1.5 mm²
Connecting Capacity Supply Circuit	Rigid 1 x 2.5 mm²
Tightening Torque	Control Circuit 0.5 N·m Main Circuit 45 N·m Supply Circuit 0.5 N·m
Product Main Type	PSTB840

Environmental

Ambient Air Temperature	Operation 0 ... +50 °C Storage -25 ... +70 °C
RoHS Status	No declaration needed

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SFA1-76
Environmental Information	1SFC132015D0201
Instructions and Manuals	1SFC132003M0201
RoHS Information	1SFC132035D0201

Container Information

Package Level 1 Width	500 mm
Package Level 1 Depth / Length	600 mm
Package Level 1 Height	460 mm
Package Level 1 Gross Weight	72 kg
Package Level 1 EAN	7320500255674
Package Level 1 Units	1 piece

Classifications

Object Classification Code	Q
ETIM 4	EC002572 - Electronic motor control and protection device
ETIM 5	EC002572 - Electronic motor control and protection device
eClass	V11.0 : 27370907
UNSPSC	39121521

Categories

Drives → Softstarters → Softstarters → PST(B) Softstarters → PST105

Low Voltage Products and Systems → Control Products → Softstarters → Softstarters → PST(B) Softstarters → PST105

