

No longer available SIMATIC IPC227D (Nanobox PC) 1x DVI-I graphics card connection; 2x 10/100/1000 Mbps Ethernet RJ45; 4xUSB V2.0 (high current); CompactFlash slot; 24 V DC industrial power s. ATOM E640 (1.0 GHz), 1 GB RAM 250 GB HDD SATA COM1: RS232; Windows 7 SP1, MUI (SSD/HD, from 1 GHz) without SIMATIC software Device type: Basic standard mounting rail

Installation type/mounting	
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	24 V DC
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Intel Atom E6x0
Drives	
Hard disk	CF or SSD or HD
SSD	Yes; ≥ 240 GB optional
Memory	
Main memory	512 MB to 2 GB
Capacity of main memory, max.	2 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte
Hardware configuration	
Slots	
• free slots	1x PCIe (x1) (optional)
• Number of compact flash slots	1; CompactFlash
Interfaces	
USB port	4x USB 2.0 high speed/high current
Connection for keyboard/mouse	USB / USB
serial interface	COM1: 1x RS 232 or RS 485 or CAN
Video interfaces	
• Graphics interface	DVI-D
Industrial Ethernet	
• Industrial Ethernet interface	2x Fast Ethernet
— 100 Mbps	Yes
— 1000 Mbps	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Watchdog	Yes
• Status LEDs	Yes
• Fan	No
Degree and class of protection	
IP (at the front)	IP20
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
KC approval	Yes
Dust protection	Protection against foreign bodies > 1 mm
Marine approval	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes

• Lloyds Register of Shipping (LRS)	Yes
Ambient conditions	
Ambient temperature during operation	
• Ambient temperature during operation	0 °C to 50 °C
Operating systems	
pre-installed operating system	Windows 7 Ultimate (Multi-Language) 32-bit / 64-bit
without operating system	Yes
pre-installed operating system	
• Windows XP Professional	Yes
• Windows 7	Yes
last modified:	3/11/2022 