

	S7-300 FRONT CONN. 40 TO DB25F 3M
	Cable with front connector for SIMATIC S7-300 40 pole (6ES7392-1AM00-0AA0) on 25 pole D-SUB socket for ET200M; 0.50 mm <sup>2</sup> Length = 3 m
target system	SIMATIC S7-300 PCS7 MTA
product type designation	MTA
product designation	Pre-assembled front connector MTA
Product properties, functions, components / general / header	
wire length	3 m
design of cable	Round cable
material / of the connection cable sheath	PVC
color / of cable sheath	Black
outer diameter / of cable sheath	10.6 mm; bundled single cores
conductor cross section / rated value	0.5 mm <sup>2</sup>
number of channels	40
number of poles	40; of the front connector
Operating data / header	
operating voltage / at DC	
• rated value	24 V
• maximum	30 V
ambient temperature	
• during storage	-30 ... +70 °C
• during operation	0 ... 60 °C
General data / header	
certificate of suitability / cULus approval	No
suitability for interaction	
• input card PLC	No
• PLC output card	Yes
suitability for use	
• digital signal transmission	Yes
• analog signal transmission	No
type of electrical connection	
• in the field	Connector strip
• on enclosure	Screw-type terminal
reference code / according to IEC 81346-2	WG
net weight	0.921 kg

