

| | |
|--|--|
| | S7-300 FRONTSTECKER 20 TO DB25F 3M NEU |
| | Cable with front connector for SIMATIC S7-300 20 pole (6ES7392-1AJ00-0AA0) on 25 pole D-SUB socket for ET200M; 0.14 mm2 Length = 3 m |
| target system | SIMATIC S7-300 PCS7 MTA |
| product type designation | MTA |
| product designation | Pre-assembled front connector MTA |
| Product properties, functions, components / general / header | |
| wire length | 3 m |
| design of cable | Round cable |
| material / of the connection cable sheath | PVC |
| color / of cable sheath | Black |
| outer diameter / of cable sheath | 7.6 mm; bundled single cores |
| conductor cross section / rated value | 0.5 mm² |
| number of channels | 20 |
| number of poles | 20; of the front connector |
| Operating data / header | |
| operating voltage / at DC | |
| • rated value | 24 V |
| • maximum | 30 V |
| ambient temperature | |
| • during storage | -30 ... +70 °C |
| • during operation | 0 ... 60 °C |
| General data / header | |
| certificate of suitability / cULus approval | No |
| suitability for interaction | |
| • input card PLC | Yes |
| • PLC output card | Yes |
| suitability for use | |
| • digital signal transmission | Yes |
| • analog signal transmission | Yes |
| type of electrical connection | |
| • in the field | Connector strip |
| • on enclosure | Screw-type terminal |
| reference code / according to IEC 81346-2 | WG |
| net weight | 0.42 kg |

