SIEMENS

Data sheet

6ES7922-3BJ00-0AS0

	S7-300 FRONT CONN. 40 TO DB50F 8M
	Cable with front connector for SIMATIC S7-300 40-pole (6ES7392-1AM00-0AA0) on 50 pole D-sub socket for ET 200M; 0.14 mm2 Length = 8 m
target system	SIMATIC S7-300 PCS7 MTA
product type designation	MTA
product designation	Pre-assembled front connector MTA
Product properties, functions, components / general / header	
wire length	8 m
design of cable	Round cable
material / of the connection cable sheath	PVC
color / of cable sheath	Black
outer diameter / of cable sheath	9.8 mm; bundled single cores
conductor cross section / rated value	0.5 mm²
number of channels	40
number of poles	40; of the front connector
Operating data / header	
operating voltage / at DC	
rated value	24 V
• maximum	30 V
ambient temperature	
during storage	-30 +70 °C
 during operation 	0 60 °C
General data / header	
certificate of suitability / cULus approval	No
suitability for interaction	
input card PLC	Yes
PLC output card	Yes
suitability for use	
 digital signal transmission 	Yes
 analog signal transmission 	Yes
type of electrical connection	
• in the field	Connector strip
• on enclosure	Screw-type terminal
reference code / according to IEC 81346-2	WG
net weight	1.551 kg

C