

MLFB-Ordering data

6FC5370-6AA00-0AA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Rated data

**Input voltage** DC 24 V +20 % -15 %

**Power consumption, max.** 60 W

### General tech. specifications

**Mains buffering time** 3 ms, 20 ms mit SITOP smart power supply

### Mechanical data

**Mounting position** Vertical

**Operator panel** Vertical

**Net weight** 4.50 kg (9.92 lb)

**Width** 310.0 mm (12.20 in)

**Height** 380.0 mm (14.96 in)

**Depth** 105.0 mm (4.13 in)

### Ambient conditions

#### Ambient temperature

**Operation on the front** 0 ... 45 °C (32 ... 113 °F)

**Operation at the rear** 0 ... 55 °C (32 ... 131 °F)

**Storage** -25 ... 55 °C (-13 ... 131 °F)

**Transport** -20 ... 60 °C (-4 ... 140 °F)

#### Relative humidity

**Operation** 5 ... 90 %

**Storage** 10 ... 100 %

**Transport** 5 ... 95 %

### Degree of protection

**Front side** IP65 With the front flap closed

**Rear side** IP20 / UL open type