SIEMENS

Data sheet 3RT2934-5AL21

magnetic coil 230 V AC, 50/60 Hz, for contactors 3RT2.3.-.A



product brand name	SIRIUS
product category	Solenoid coils
product designation	Magnet coil
General technical data	
Substance Prohibitance (Date)	10/01/2014
Weight	0.12 kg
type of voltage of the control supply voltage	AC
control supply voltage 1 at AC	
 at 50 Hz rated value 	230 V
at 60 Hz rated value	230 V
control supply voltage frequency	
1 rated value	50 Hz
• 2 rated value	60 Hz
operating range factor control supply voltage rated value of magnet coil at AC	
● at 50 Hz	0.8 1.1
● at 60 Hz	0.85 1.1
apparent pick-up power of magnet coil at AC	
● at 50 Hz	210 VA
● at 60 Hz	188 VA
inductive power factor with closing power of the coil	
● at 50 Hz	0.69
● at 60 Hz	0.65
apparent holding power of magnet coil at AC	
● at 50 Hz	17.2 VA
• at 60 Hz	16.5 VA
inductive power factor with the holding power of the coil	
● at 50 Hz	0.39
● at 60 Hz	0.36
Approvals Certificates	

General Product Approval

Confirmation





EMV



Marine / Shipping

Marine / Shipping

other

Environment





Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)


https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2934-5AL21


Cax online generator

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3RT2934-5AL21

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2934-5AL21&lang=en





last modified:

1/10/2024