



power contactor, AC-3e/AC-3, 80 A, 37 kW / 400 V, 3-pole, 21-33 V AC/DC, 50/60 Hz, with integrated varistor, auxiliary contacts: 1 NC, main circuit: screw terminal, control and auxiliary circuit: spring-loaded terminal, size: S2, F-PLC-IN

|  |   |
|--|---|
| product brand name   | SIRIUS  |
| product designation  | Power contactor   |
| product type designation   | 3RT2  |
| <b>General technical data</b>  |   |
| size of contactor  | S2  |
| product extension  |   |
| • function module for communication  | No  |
| • auxiliary switch   | Yes   |
| power loss [W] for rated value of the current  |   |
| • at AC in hot operating state   | 17.1 W  |
| • at AC in hot operating state per pole  | 5.7 W   |
| • without load current share typical   | 1.6 W   |
| type of calculation of power loss depending on pole  | quadratic   |
| insulation voltage   |   |
| • of main circuit with degree of pollution 3 rated value   | 690 V   |
| • of auxiliary circuit with degree of pollution 3 rated value  | 690 V   |
| surge voltage resistance   |   |
| • of main circuit rated value  | 6 kV  |
| • of auxiliary circuit rated value   | 6 kV  |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V   |
| shock resistance at rectangular impulse  |   |
| • at AC  | 7.7g / 5 ms, 4.5g / 10 ms   |
| • at DC  | 7.7g / 5 ms, 4.5g / 10 ms   |
| shock resistance with sine pulse   |   |
| • at AC  | 12g / 5 ms, 7g / 10 ms  |
| • at DC  | 12g / 5 ms, 7g / 10 ms  |
| mechanical service life (operating cycles)   |   |
| • of contactor typical   | 5 000 000   |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000   |
| • of the contactor with added auxiliary switch block typical   | 5 000 000   |
| reference code according to IEC 81346-2  | Q   |
| Substance Prohibitance (Date)  | 01/29/2021  |
| SVHC substance name  | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5 |
| Weight   | 1.14 kg   |
| <b>Ambient conditions</b>  |   |
| installation altitude at height above sea level maximum  | 2 000 m   |
| ambient temperature  |   |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> </ul>  | -25 ... +60 °C<br>-55 ... +80 °C   |
| <b>relative humidity minimum</b>  | 10 %   |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>   | 95 %   |
| <b>Main circuit</b>   |  |
| <b>number of poles for main current circuit</b>   | 3  |
| <b>number of NO contacts for main contacts</b>  | 3  |
| <b>operating voltage</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-3 rated value maximum</li> <li>• at AC-3e rated value maximum</li> </ul>   | 690 V<br>690 V   |
| <b>operational current</b>  |  |
| <ul style="list-style-type: none"> <li>• at AC-1 at 400 V at ambient temperature 40 °C rated value</li> <li>• at AC-1 <ul style="list-style-type: none"> <li>— up to 690 V at ambient temperature 40 °C rated value</li> <li>— up to 690 V at ambient temperature 60 °C rated value</li> </ul> </li> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>• at AC-3e <ul style="list-style-type: none"> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>• at AC-4 at 400 V rated value</li> <li>• at AC-5a up to 690 V rated value</li> <li>• at AC-5b up to 400 V rated value</li> <li>• at AC-6a <ul style="list-style-type: none"> <li>— up to 230 V for current peak value n=20 rated value</li> <li>— up to 400 V for current peak value n=20 rated value</li> <li>— up to 500 V for current peak value n=20 rated value</li> <li>— up to 690 V for current peak value n=20 rated value</li> </ul> </li> <li>• at AC-6a <ul style="list-style-type: none"> <li>— up to 230 V for current peak value n=30 rated value</li> <li>— up to 400 V for current peak value n=30 rated value</li> <li>— up to 500 V for current peak value n=30 rated value</li> <li>— up to 690 V for current peak value n=30 rated value</li> </ul> </li> </ul> | 90 A<br><br><br>90 A<br>80 A<br><br>80 A<br>80 A<br>80 A<br>58 A<br><br>80 A<br>80 A<br>58 A<br>55 A<br>79.2 A<br>66.4 A<br><br>70 A<br>70 A<br>70 A<br>58 A<br><br>46.7 A<br>46.7 A<br>46.7 A<br>46.7 A |
| minimum cross-section in main circuit at maximum AC-1 rated value   | 35 mm <sup>2</sup>   |
| <b>operational current for approx. 200000 operating cycles at AC-4</b>  |  |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> <li>• at 690 V rated value</li> </ul>  | 30 A<br>24 A   |
| <b>operational current</b>  |  |
| <ul style="list-style-type: none"> <li>• at 1 current path at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• with 2 current paths in series at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• with 3 current paths in series at DC-1</li> </ul>   | 55 A<br>23 A<br>4.5 A<br>1 A<br>0.4 A<br>0.25 A<br><br>55 A<br>45 A<br>45 A<br>5 A<br>1 A<br>0.8 A   |

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul>   | 55 A<br>55 A<br>55 A<br>45 A<br>2.9 A<br>1.4 A  |
| <ul style="list-style-type: none"> <li>● <b>at 1 current path at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>   | 35 A<br>6 A<br>1 A<br>0.1 A<br>0.06 A   |
| <ul style="list-style-type: none"> <li>● <b>with 2 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>  | 55 A<br>45 A<br>25 A<br>5 A<br>0.27 A<br>0.16 A   |
| <ul style="list-style-type: none"> <li>● <b>with 3 current paths in series at DC-3 at DC-5</b> <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul>  | 55 A<br>55 A<br>55 A<br>25 A<br>0.6 A<br>0.35 A   |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-2 at 400 V rated value</li> <li>● at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul> | 37 kW<br><br>22 kW<br>37 kW<br>37 kW<br>45 kW<br><br>22 kW<br>37 kW<br>37 kW<br>45 kW   |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>  | 15.8 kW<br>21.8 kW  |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>   | 48 400 VA<br>60 600 VA<br>69 300 VA   |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>  | 18 600 VA<br>32 300 VA<br>40 400 VA<br>55 800 VA  |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> <li>● limited to 5 s switching at zero current maximum</li> <li>● limited to 10 s switching at zero current maximum</li> <li>● limited to 30 s switching at zero current maximum</li> <li>● limited to 60 s switching at zero current maximum</li> </ul>  | 1 298 A; Use minimum cross-section acc. to AC-1 rated value<br>898 A; Use minimum cross-section acc. to AC-1 rated value<br>640 A; Use minimum cross-section acc. to AC-1 rated value<br>414 A; Use minimum cross-section acc. to AC-1 rated value<br>333 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>● at AC</li> <li>● at DC</li> </ul>  | 1 000 1/h<br>1 000 1/h  |

|   |                                |
|---|--------------------------------|
| <b>operating frequency</b>  |                                |
| • at AC-1 maximum   | 700 1/h                        |
| • at AC-2 maximum   | 350 1/h                        |
| • at AC-3 maximum   | 500 1/h                        |
| • at AC-3e maximum  | 500 1/h                        |
| • at AC-4 maximum   | 150 1/h                        |
| <b>Control circuit/ Control</b>   |                                |
| <b>type of voltage of the control supply voltage</b>                                  | AC/DC                          |
| <b>control supply voltage at AC</b>   |                                |
| • at 50 Hz rated value  | 21 ... 33 V                    |
| • at 60 Hz rated value  | 21 ... 33 V                    |
| <b>control supply voltage at DC rated value</b>                                       | 21 ... 33 V                    |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> |                                |
| • initial value   | 0.8                            |
| • full-scale value  | 1.1                            |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> |                                |
| • at 50 Hz  | 0.8 ... 1.1                    |
| • at 60 Hz  | 0.8 ... 1.1                    |
| <b>type of PLC-control input according to IEC 60947-1</b>                             | Type 1                         |
| <b>consumed current at PLC-control input according to IEC 60947-1 maximum</b>         | 11 mA                          |
| <b>voltage at PLC-control input rated value</b>                                       | 24 V                           |
| <b>operating range factor of the voltage at PLC-control input</b>                     | 0.8 ... 1.1                    |
| <b>design of the surge suppressor</b>   | with varistor                  |
| <b>inrush current peak</b>  | 2.2 A                          |
| <b>duration of inrush current peak</b>  | 100 µs                         |
| <b>locked-rotor current mean value</b>  | 1.6 A                          |
| <b>locked-rotor current peak</b>  | 2.6 A                          |
| <b>duration of locked-rotor current</b>   | 230 ms                         |
| <b>holding current mean value</b>   | 0.075 A                        |
| <b>apparent pick-up power of magnet coil at AC</b>                                    |                                |
| • at 50 Hz  | 40 VA                          |
| • at 60 Hz  | 40 VA                          |
| <b>apparent holding power</b>   |                                |
| • at minimum rated control supply voltage at DC                                       | 2 VA                           |
| • at maximum rated control supply voltage at DC                                       | 2 VA                           |
| <b>apparent holding power</b>   |                                |
| • at minimum rated control supply voltage at AC                                       |                                |
| — at 50 Hz  | 2 VA                           |
| — at 60 Hz  | 2 VA                           |
| • at maximum rated control supply voltage at AC                                       |                                |
| — at 50 Hz  | 2 VA                           |
| — at 60 Hz  | 2 VA                           |
| <b>apparent holding power of magnet coil at AC</b>                                    |                                |
| • at 50 Hz  | 2 VA                           |
| • at 60 Hz  | 2 VA                           |
| <b>inductive power factor with the holding power of the coil</b>                      |                                |
| • at 50 Hz  | 0.95                           |
| • at 60 Hz  | 0.95                           |
| <b>closing power of magnet coil at DC</b>   | 40 W                           |
| <b>holding power of magnet coil at DC</b>   | 1.6 W                          |
| <b>closing delay</b>  |                                |
| • at AC   | 35 ... 110 ms                  |
| • at DC   | 35 ... 110 ms                  |
| <b>opening delay</b>  |                                |
| • at AC   | 30 ... 55 ms                   |
| • at DC   | 30 ... 55 ms                   |
| <b>recovery time after power failure typical</b>                                      | 2.1 s                          |
| <b>arcing time</b>  | 10 ... 20 ms                   |
| <b>control version of the switch operating mechanism</b>                              | Fail-safe PLC input (F-PLC-IN) |

|   |  |
|---|--|
| <b>Auxiliary circuit</b>  |  |
| number of NC contacts for auxiliary contacts instantaneous contact  | 1  |
| number of NO contacts for auxiliary contacts instantaneous contact  | 0  |
| operational current at AC-12 maximum  | 10 A   |
| <b>operational current at AC-15</b>   |  |
| • at 230 V rated value  | 10 A   |
| • at 400 V rated value  | 3 A  |
| • at 500 V rated value  | 2 A  |
| • at 690 V rated value  | 1 A  |
| <b>operational current at DC-12</b>   |  |
| • at 24 V rated value   | 10 A   |
| • at 48 V rated value   | 6 A  |
| • at 60 V rated value   | 6 A  |
| • at 110 V rated value  | 3 A  |
| • at 125 V rated value  | 2 A  |
| • at 220 V rated value  | 1 A  |
| • at 600 V rated value  | 0.15 A   |
| <b>operational current at DC-13</b>   |  |
| • at 24 V rated value   | 10 A   |
| • at 48 V rated value   | 2 A  |
| • at 60 V rated value   | 2 A  |
| • at 110 V rated value  | 1 A  |
| • at 125 V rated value  | 0.9 A  |
| • at 220 V rated value  | 0.3 A  |
| • at 600 V rated value  | 0.1 A  |
| <b>contact reliability of auxiliary contacts</b>  | 1 faulty switching per 100 million (17 V, 1 mA)  |
| <b>UL/CSA ratings</b>   |  |
| <b>full-load current (FLA) for 3-phase AC motor</b>   |  |
| • at 480 V rated value  | 65 A   |
| • at 600 V rated value  | 62 A   |
| <b>yielded mechanical performance [hp]</b>  |  |
| • for single-phase AC motor   |  |
| — at 110/120 V rated value  | 5 hp   |
| — at 230 V rated value  | 15 hp  |
| • for 3-phase AC motor  |  |
| — at 200/208 V rated value  | 20 hp  |
| — at 220/230 V rated value  | 25 hp  |
| — at 460/480 V rated value  | 50 hp  |
| — at 575/600 V rated value  | 60 hp  |
| <b>contact rating of auxiliary contacts according to UL</b>   | A600 / P600  |
| <b>Short-circuit protection</b>   |  |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V | C characteristic: 10 A; 0.4 kA   |
| <b>design of the fuse link</b>  |  |
| • for short-circuit protection of the main circuit  |  |
| — with type of coordination 1 required  | gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)   |
| — with type of assignment 2 required  | gG: 160A (690V,100kA), aM: 80A (690V,100kA), BS88: 125A (415V,80kA)  |
| • for short-circuit protection of the auxiliary switch required   | gG: 10 A (500 V, 1 kA)   |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| fastening method side-by-side mounting  | Yes  |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715   |
| <b>height</b>   | 114 mm   |
| <b>width</b>  | 55 mm  |
| <b>depth</b>  | 130 mm   |
| <b>required spacing</b>   |  |
| • with side-by-side mounting  |  |
| — forwards  | 10 mm  |

|  |  |
|--|--|
| — upwards  | 10 mm  |
| — downwards  | 10 mm  |
| — at the side  | 0 mm   |
| • for grounded parts   |  |
| — forwards   | 10 mm  |
| — upwards  | 10 mm  |
| — at the side  | 6 mm   |
| — downwards  | 10 mm  |
| • for live parts   |  |
| — forwards   | 10 mm  |
| — upwards  | 10 mm  |
| — downwards  | 10 mm  |
| — at the side  | 6 mm   |
| <b>Connections/ Terminals</b>  |  |
| <b>type of electrical connection</b>                                 |  |
| • for main current circuit   | screw-type terminals   |
| • for auxiliary and control circuit                                  | spring-loaded terminals  |
| • at contactor for auxiliary contacts                                | Spring-type terminals  |
| • of magnet coil   | Spring-type terminals  |
| <b>type of connectable conductor cross-sections</b>                  |  |
| • for main contacts  |  |
| — solid or stranded  | 2x (1 ... 35 mm <sup>2</sup> ), 1x (1 ... 50 mm <sup>2</sup> ) |
| — finely stranded with core end processing                           | 2x (1 ... 25 mm <sup>2</sup> ), 1x (1 ... 35 mm <sup>2</sup> ) |
| • for AWG cables for main contacts                                   | 2x (18 ... 2), 1x (18 ... 1)                                   |
| <b>connectable conductor cross-section for main contacts</b>         |  |
| • finely stranded with core end processing                           | 1 ... 35 mm <sup>2</sup>                                       |
| <b>connectable conductor cross-section for auxiliary contacts</b>    |  |
| • solid or stranded  | 0.5 ... 2.5 mm <sup>2</sup>                                    |
| • finely stranded with core end processing                           | 0.5 ... 1.5 mm <sup>2</sup>                                    |
| • finely stranded without core end processing                        | 0.5 ... 2.5 mm <sup>2</sup>                                    |
| <b>type of connectable conductor cross-sections</b>                  |  |
| • for auxiliary contacts   |  |
| — solid or stranded  | 2x (0.5 ... 2.5 mm <sup>2</sup> )                              |
| — finely stranded with core end processing                           | 2x (0.5 ... 1.5 mm <sup>2</sup> )                              |
| — finely stranded without core end processing                        | 2x (0.5 ... 2.5 mm <sup>2</sup> )                              |
| • for AWG cables for auxiliary contacts                              | 2x (20 ... 14)   |
| <b>AWG number as coded connectable conductor cross section</b>       |  |
| • for main contacts  | 18 ... 1   |
| • for auxiliary contacts   | 20 ... 14  |
| <b>Safety related data</b>   |  |
| <b>product function</b>  |  |
| • mirror contact according to IEC 60947-4-1                          | Yes  |
| • positively driven operation according to IEC 60947-5-1             | No   |
| • suitable for safety function                                       | Yes  |
| suitability for use safety-related switching OFF                     | Yes  |
| <b>safe state</b>  | off  |
| <b>test wear-related service life necessary</b>                      | Yes  |
| <b>diagnostics test interval by internal test function maximum</b>   | 28 800 s   |
| <b>stop category according to IEC 60204-1</b>                        | 0  |
| <b>proportion of dangerous failures</b>                              |  |
| • with low demand rate according to SN 31920                         | 40 %   |
| • with high demand rate according to SN 31920                        | 73 %   |
| <b>B10 value with high demand rate according to SN 31920</b>         | 1 000 000  |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b> | 100 FIT  |
| <b>MTBF</b>  | 52 a   |
| IEC 62061  |  |
| <b>Safety Integrity Level (SIL) according to IEC 62061</b>           | SIL 2  |
| PFHD with high demand rate according to IEC 62061                    | 7.7E-8 1/h   |
| ISO 13849  |  |

|   |  |
|---|--|
| performance level (PL) according to ISO 13849-1         | PL c   |
| category according to ISO 13849-1                       | 2  |
| device type according to ISO 13849-1                    | 1  |
| overdimensioning according to ISO 13849-2 necessary     | Yes  |
| IEC 61508   |  |
| Safety Integrity Level (SIL) according to IEC 61508     | 2  |
| safety device type according to IEC 61508-2             | Type B   |
| PFHD with high demand rate according to IEC 61508       | 7.7E-8 1/h                                       |
| PFDAvg with low demand rate according to IEC 61508      | 0.0067   |
| Safe failure fraction (SFF)                             | 96 %   |
| hardware fault tolerance according to IEC 61508         | 0  |
| T1 value of service life according to IEC 61508         | 20 a   |
| Electrical Safety                                       |  |
| protection class IP on the front according to IEC 60529 | IP20   |
| touch protection on the front according to IEC 60529    | finger-safe, for vertical contact from the front |

#### Approvals Certificates

##### General Product Approval



[Confirmation](#)



[KC](#)

| General Product Approval | EMV | Functional Safety | Test Certificates | Marine / Shipping |
|--------------------------|-----|-------------------|-------------------|-------------------|
|--------------------------|-----|-------------------|-------------------|-------------------|



[Type Examination Certificate](#)

[Type Test Certificates/Test Report](#)



| Marine / Shipping | other | Railway | Environment |
|-------------------|-------|---------|-------------|
|-------------------|-------|---------|-------------|



[Confirmation](#)

[Special Test Certificate](#)

[Environmental Confirmations](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2038-3SB30>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2038-3SB30>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2038-3SB30>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2038-3SB30&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2038-3SB30&lang=en)

##### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2038-3SB30/char>

##### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2038-3SB30&objecttype=14&gridview=view1>





