## **Standard Models**

## **CPU Rack**

Name			Specification	าร		Model number	Standards
CPU Units (Model numbers with suffix ZE.) (All models incorporate a clock function and slot for the Communications Board except for the CPU11-E.)	UM	DM	EM	I/O points	RS-232C		U, C, N, L, CE
	3.2K words	4K words		640	No	C200HE-CPU11-ZE	
	7.2K	6K words		880	No	C200HE-CPU32-ZE	
	words				Yes	C200HE-CPU42-ZE	
	15.2K words		6K words		No	C200HG-CPU33-ZE	
					Yes	C200HG-CPU43-ZE	
				1,184	No	C200HG-CPU53-ZE	1
					Yes	C200HG-CPU63-ZE	1
	31.2K words		6K words x 3	880	No	C200HX-CPU34-ZE	
					Yes	C200HX-CPU44-ZE	
				1,184	No	C200HX-CPU54-ZE	
					Yes	C200HX-CPU64-ZE	1
	63.2K words		6K words x 8			C200HX-CPU65-ZE	
			6K words x 16			C200HX-CPU85-ZE	
CPU Units (Model numbers without suffix ZE) (All models incorporate a clock function and slot for the Communications Board except for the CPU11-E.)	3.2K words	4K words		640	No	C200HE-CPU11-E	
	7.2K	6K words	 6K words	880	No	C200HE-CPU32-E	
	words				Yes	C200HE-CPU42-E	
	15.2K				No	C200HG-CPU33-E	
	words				Yes	C200HG-CPU43-E	
				1,184	No	C200HG-CPU53-E	
					Yes	C200HG-CPU63-E	1
	31.2K		6K words	880	No	C200HX-CPU34-E	
	words		x 3		Yes	C200HX-CPU44-E	
				1,184	No	C200HX-CPU54-E	
					Yes	C200HX-CPU64-E	
Power Supply Units	100 to 120/200 to 240 VAC					C200HW-PA204	1
	100 to 120/200 to 240 VAC (with 24-VDC output terminals)					C200HW-PA204S	1
	100 to 120/200 to 240 VAC (with output contacts during operation)					C200HW-PA204R	U, C
	100 to 120/200 to 240 VAC (with output contacts during operation) Output capacity: 9 A at 5 VDC					C200HW-PA209R	U, C, N, L, CE
	Power supply voltage: 24VDC					C200HW-PD024	
CPU I/O Backplanes 3 slots						C200HW-BC031	
	5 slots					C200HW-BC051	
	8 slots					C200HW-BC081-V1	U, C, CE
	10 slots					C200HW-BC101-V1	
Communications Boards	Communications port for SYSMAC LINK					C200HW-COM01	U, C, N, L,
	RS-232C p				C200HW-COM02-V1	CE	
	RS-422/485 port					C200HW-COM03-V1	
	Communications port for the SYSMAC LINK Unit and a protocol macro function					C200HW-COM04-EV1	
	Two RS-232C ports and a protocol macro function					C200HW-COM05-EV1	1
	RS-422/485 port, an RS-232C port, and a protocol macro function					C200HW-COM06-EV1	