SIEMENS

Data sheet 6XV1821-1CT20

product type designation
product description

suitability for use

PROFIBUS PCF Fiber Optic standard cable

Cable for indoor applications

PCF fiber-optic cable with plastic cladding, preferred length, preassembled PROFIBUS PCF Fiber Optic, with 4 PCF Simplex connectors, length 200 m.



suitability for use	Cable for indoor applications
version of the assembled FO cable	Assembled with four Simplex connectors
cable designation	I-V(ZN)Y 2K 200/230
wire length	200 m
ptical data	
attenuation factor per length	
• at 650 nm / maximum	10 dB/km
• at 660 nm / maximum	10 dB/km
bandwidth length product	
• at 650 nm	17 GHz·m
nechanical data	
number of fibers / per FOC core	1
number of FO cores / per FOC cable	2
version of the FO conductor fiber	Step index fiber 200/230 µm
outer diameter	
 of the optical fibers 	200 μm
 of the optical fiber sheath 	230 μm
of the FOC core sheath	2.2 mm
symmetrical deviation / of the outer diameter of the FOC core sheath	0.1 mm
outer diameter / of the cable	4.7 mm
material	
 of the fiber-optic cable core 	Quartz glass
 of the optical fiber sheath 	Fluoridated special polymer
 of the FOC core sheath 	PVC
 of the fiber-optic cable sheath 	PVC
of the strain relief	Kevlar fibers
color	
 of the FOC core sheath 	orange/black
of cable sheath	Violet
bending radius	
with single bend / minimum permissible	47 mm
with multiple bends / minimum permissible	70 mm
tensile load	
 during installation / short-term 	800 N
during operation / maximum	200 N
short-term shear force per length	100 N/cm
weight per length	22 kg/km

ambient conditions		
ambient temperature		
during operation	-30 +70 °C	
	-30 +70 °C	
during storageduring transport	-30 +70 °C	
	-5 +70 °C	
during installation fire behavior		
fire behavior	flame-resistant acc. to IEC 60332-1-2	
chemical resistance	conditional resistance	
• to mineral oil	conditional resistance	
• to grease	conditional resistance	
radiological resistance / to UV radiation	not resistant	
protection class IP	IP20	
product features, product functions, product components / ge	nerai	
product feature	A.	
• halogen-free	No	
• silicon-free	Yes	
product component / rodent protection	No	
wire length		
for PCF FOC / with PROFIBUS / maximum	400 m	
standards, specifications, approvals		
certificate of suitability		
RoHS conformity	Yes	
reference code		
 according to IEC 81346-2 	WH	
• according to IEC 81346-2:2019	WHA	
further information / internet links		
internet link		
 to website: Selection guide for cables and connectors 	https://support.industry.siemens.com/cs/ww/en/view/109766358	
 to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud	
 to website: Industrial communication 	https://www.siemens.com/simatic-net	
to web page: SiePortal	https://sieportal.siemens.com/	
 to website: Image database 	https://www.automation.siemens.com/bilddb	
to website: CAx-Download-Manager	https://www.siemens.com/cax	
to website: Industry Online Support	https://support.industry.siemens.com	
security information / header		
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under	

Approvals / Certificates

General Product Approval



Declaration of Conformity





https://www.siemens.com/cert. (V4.7)

Manufacturer Declaration

subscribe to the Siemens Industrial Cybersecurity RSS Feed under



General Product Approval	Marine / Shipping	other	Environment
--------------------------	-------------------	-------	-------------





<u>Confirmation</u> <u>Confirmation</u>

last modified: 8/9/2024 🖸