SIEMENS

Data sheet

6GK5792-8DN00-0AA6

product type designation



Antenna ANT792-8DN

ANT792-8DN IWLAN antenna with strong directional effect incl. N-female plug: 14 dBi, IP23, outdoor, (-40-+70 °C); 2.4 GHz, Wi-Fi compliance observe national approvals; mounting on wall or mast, compact instructions as hard copy German/English, scope of delivery: 1x ANT792-8DN, 1x mounting aid for alignment 1x mounting aid for alignment .

| radio frequencies | |
|---|---|
| type of wireless network / is supported | WLAN |
| operating frequency | |
| for WLAN in 2.4 GHz frequency band | 2.4 2.7 GHz |
| electrical data | |
| antenna gain compared to spherical radiator | |
| • of the WLAN antenna / in the 2.4 GHz frequency band | 14 dB |
| impedance | 50 Ω |
| polarization | Linear Vertical |
| radiation characteristic | directional |
| standing wave ratio (VSWR) / maximum | 1.5 |
| radiating angle of the antenna | |
| in the 2.4 GHz frequency band / horizontal | 35° |
| • in the 2.4 GHz frequency band / vertical | 30° |
| number of electrical connections / of the antenna | 1 |
| type of electrical connection / of the antenna | N-Connector |
| design of plug-in connection | female |
| angle of inclination / downward / maximum | 0° |
| front-to-back ratio | 20 dB |
| mechanical data | |
| material | |
| of outer shell | ASA |
| ambient conditions | |
| ambient temperature | |
| during operation | -40 +80 °C |
| during storage | -40 +80 °C |
| during transport | -40 100 0 |
| • during transport | -40 +80 °C |
| protection class IP | |
| - | -40 +80 °C |
| protection class IP wind load / maximum | -40 +80 °C IP23 |
| protection class IP wind load / maximum | -40 +80 °C IP23 |
| protection class IP wind load / maximum design, dimensions and weights | -40 +80 °C IP23 57 N; at 160 km/h |
| protection class IP wind load / maximum design, dimensions and weights width | -40 +80 °C IP23 57 N; at 160 km/h |
| protection class IP wind load / maximum design, dimensions and weights width height | -40 +80 °C IP23 57 N; at 160 km/h 200 mm 200 mm |
| protection class IP wind load / maximum design, dimensions and weights width height depth | -40 +80 °C IP23 57 N; at 160 km/h 200 mm 200 mm 43 mm |
| protection class IP wind load / maximum design, dimensions and weights width height depth net weight | -40 +80 °C IP23 57 N; at 160 km/h 200 mm 200 mm 43 mm |
| protection class IP wind load / maximum design, dimensions and weights width height depth net weight fastening method | -40 +80 °C IP23 57 N; at 160 km/h 200 mm 200 mm 43 mm 500 g |
| protection class IP wind load / maximum design, dimensions and weights width height depth net weight fastening method • mast mounting | -40 +80 °C IP23 57 N; at 160 km/h 200 mm 200 mm 43 mm 500 g Yes |

| product features, product functions, product components / general | |
|---|---|
| product feature / silicon-free | Yes |
| standards, specifications, approvals | |
| certificate of suitability | |
| RoHS conformity | Yes |
| wireless approval | Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen |
| reference code / according to IEC 81346-2:2019 | TFB |
| further information / internet links | |
| internet link | |
| to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| to web page: WLAN country approval | https://www.siemens.com/wireless-approvals |
| to website: Industrial communication | https://www.siemens.com/simatic-net |
| to web page: SiePortal | https://sieportal.siemens.com/ |
| to website: Image database | https://www.automation.siemens.com/bilddb |
| to website: CAx-Download-Manager | https://www.siemens.com/cax |
| to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7) |

last modified:

12/10/2024